

Crimping Tool HHT SERIES

13-14 Ton
10,000 psi

The industry standard; durable,
long-lasting hand hydraulic tools.

COMPRESSION TOOLS FOR U- OR SHELL-TYPE DIES

- Two-speed pump for rapid ram advance*
- High-strength fiberglass handles
- C-shaped head with 360° rotation for ease of accessibility**
- Capacity for all U- or shell-type dies
- Twist handle release
- High-pressure safety relief valve
- Push-button system for ease of die insertion and removal
- With Carrying Bag

C12-TON-B

- C-shaped head with 180° rotation for ease of accessibility
- Trigger release handle



HYDRAULIC TOOLS

Tool Model	Crimping Force U.S. tons	Operating Pressure psi	Jaw Opening in.	Crimping Capacity	Overall Length in.	Overall Depth in.	Head Width in.	Tool Weight lbs.
C12-TON-B	13.1	10,000	0.95	see below	22.81	3.0	8.56	13.6
C12-HHT-B	13.1	10,000	1.187	see below	22.12	3.00	8.64	13.6
C14-HHT-B	14.0	10,000	1.50	750	23.28	3.10	8.38	17.4

Copper	C12-HHT Crimping Capacity Aluminum	ASCR
No. 8 stranded through 500 MCM grounding terminals and splices No. 8 stranded through 250 MCM grounding taps and 3/4" ground rod No. 8 stranded through 750 MCM insulated and uninsulated terminals	No. 8 stranded through 750 MCM terminals No. 8 stranded through 350 MCM splices	No. 6 stranded through 556.5 26/7 stranding

* C12-Ton-B is a single stage pump.

** C12-Ton-B Head rotates 180°