CUTTING TOOLS FOR CABLE, WIRE AND BAR

- · Two-speed pumping system for rapid blade advance
- · Full 360° head rotation
- · Compact, lightweight design for reaching tight places
- · Twist release handle
- · High-pressure safety relief valve
- · Hinged flip-top head
- · Easy blade replacement
- · With tool bag



6-13 Ton 10,000 psi

Two-speed, long lasting construction. Top stationary blade and bottom advance blade easy field maintenance.



Tool Model	Cutting Force U.S. tons	Operating Pressure psi	Blade Opening in.	Overall Length in.	Overall Depth in.	Overall Width in.	Tool Weight lbs.
6-ННС-В	6.1	10,000	0.81	20.16	2.69	6.24	8.8
13-ННС-В	13.8	10,000	2.09	25.66	4.12	7.39	20.1

CUTTING CAPACITY — DIAMETERS (IN.)

Soft Copper Bar	Soft Aluminum Bar	Soft Steel Bolts	Reinforcing Bar	Bare Stranded Copper/Aluminum Wire	ASCR	Stranded Galvanized Steel Wire	Underground Power Cable	Wire Rope
5/8	1/2	5/8	3/8	3/4	3/4	5/8	3/4	3/4
1-1/4	1-1/4	7/8	3/4	2	2	3/4	2	1
	Bar 5/8	Bar Bar 5/8 1/2	Bar Bar Bolts 5/8 1/2 5/8	Bar Bar Bolts Bar 5/8 1/2 5/8 3/8	Bar Bolts Bar Wire 5/8 1/2 5/8 3/8 3/4	Bar Bolts Bar Wire ASCR 5/8 1/2 5/8 3/8 3/4 3/4	Bar Bolts Bar Wire ASCR Steel Wire 5/8 1/2 5/8 3/8 3/4 3/4 5/8	Bar Bolts Bar Wire ASCR Steel Wire Power Cable 5/8 1/2 5/8 3/8 3/4 3/4 5/8 3/4