

# Puller Sets






**10 ton capacity Push-Puller® set** – Contains three popular Power Team bar-type pullers in one versatile set, packed in a handy plastic storage case. Tools included permit damage-free pulling of gears, bearings, harmonic balancers, and other parts having tapped holes. Ideal for servicing off-road construction equipment and machinery.

**Multi-purpose puller set** – This new assortment of pulling tools gives you a wide range of job versatility. You get a 5 lb. slide hammer puller, hub puller, two sizes of Power Team Grip-O-Matic® jaw-type pullers, a bearing pulling attachment plus a cross-bar gear and pulley puller, all contained in a handy plastic storage case.

**Lock-on, jaw-type puller set** – Components can be assembled to create several versatile puller versions. The puller head is turned to securely lock the jaws onto the part being removed. Both a 2-way and 3-way puller head are included, plus three long-reach and three short-reach puller jaws in a plastic storage box. Easily removes gears, bearings and other press-fitted parts.

Convenient, portable puller sets that go where you do.

BEARING MAINTENANCE

Order No.	Set Contents	Description							
<b>1180</b> 10 ton Push-Puller® set, in plastic storage case. Wt., 25 lbs. 	927	10 Ton Push-Puller®; 8 <sup>3</sup> / <sub>8</sub> " reach, 2 <sup>1</sup> / <sub>8</sub> " to 7 <sup>1</sup> / <sub>4</sub> " spread. Comes with 6 <sup>3</sup> / <sub>4</sub> " puller legs, other leg sizes are available separately (See page 207).							
	522	Gear and pulley puller; spread range when used with 1/2" cap screws: 2" to 7 <sup>3</sup> / <sub>4</sub> ". Cap screws not included.							
	7393	Gear and pulley puller with standard 5 <sup>1</sup> / <sub>2</sub> " forcing screw, plus special 13" forcing screw. Includes two hex head cap screws, 3/8"-16 x 3" long. Spread range: 1 <sup>1</sup> / <sub>2</sub> " to 4 <sup>1</sup> / <sub>4</sub> ".							
<b>1181</b> Multi-purpose puller set. Wt., 25 lbs. 	1177	Slide hammer puller with 5 lb. hammer, 2-way and 3-way heads. Reversible: either two or three jaws may be used to handle both "inside" and "outside" pulling jobs.							
	7208	Hub puller. Includes a spare locknut which permits use with No. 1177 slide hammer.							
	1023	2 ton combination 2- or 3-jaw Grip-O-Matic® puller. Has 3 <sup>3</sup> / <sub>8</sub> " max. reach, 4 <sup>3</sup> / <sub>4</sub> " max. spread.							
	1027	5 ton combination 2- or 3-jaw Grip-O-Matic® puller. Has 5 <sup>1</sup> / <sub>2</sub> " max. reach, 7" max. spread.							
	7393	Bar-type gear and pulley puller with 5 <sup>1</sup> / <sub>2</sub> " long screw. Includes two hex head cap screws, 3/8"-16 x 3" long. Spread range: 1 <sup>1</sup> / <sub>2</sub> " to 4 <sup>1</sup> / <sub>4</sub> ".							
1122	Bearing pulling attachment for use with No. 1027 and No. 7393 pullers. Has 2" max. spread, 1/8" min. spread.								
<b>1182</b> Jaw-type puller set. Wt., 6.8 lbs 	<b>2-Jaw</b>		<b>3-Jaw Spread</b>						
	<b>Puller Jaws Order</b>	<b>Inside* Min. (in.)</b>	<b>Max. (in.)</b>	<b>Outside Min. (in.)</b>	<b>Max. (in.)</b>	<b>Inside* Min. (in.)</b>	<b>Max. (in.)</b>	<b>Outside Min. (in.)</b>	<b>Max. (in.)</b>
	44195	1 <sup>1</sup> / <sub>2</sub>	4 <sup>1</sup> / <sub>2</sub>	3/4	5	1 <sup>1</sup> / <sub>2</sub>	4 <sup>3</sup> / <sub>4</sub>	1	4 <sup>1</sup> / <sub>2</sub>
	44148	2 <sup>3</sup> / <sub>4</sub>	5 <sup>1</sup> / <sub>2</sub>	3/4	7 <sup>1</sup> / <sub>2</sub>	3 <sup>3</sup> / <sub>4</sub>	6 <sup>1</sup> / <sub>4</sub>	1	6 <sup>1</sup> / <sub>4</sub>

\* Can be used for internal pulling tasks when used with a slide hammer.