Toe Jacks

5.5, 11 & 27.5 Ton

Get under equipment with only 11/16" of ground clearance.


- With lifting points on the toe and on the top, these extremely rugged jacks are ideal for machine lifting, rigging, lift truck service and much more.
- Choose from 5.5-ton, 11-ton, and now, an amazing 27.5-ton lifting capacity.



- All jacks operate both vertically and horizontally.
- Base, toe and pumping assembly swivel independently, allowing the jack to work in confined areas.



The J Series Toe Jack is an extremely rugged jack used here for lift truck service.



	DIMENSIONS											
	A		В		С	D	Е	F	G	н	J	
Order	Ret.	Ext.	Ret.	Ext.								
Number	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	
J58T	11/16	93/8	143/4	23	14 ¹ / ₂	173/4	213/16	23/16	615/16	1 ⁵ /8	5 ¹ / ₈	
J109T	11/16	$10^{3}/_{8}$	16 ¹ / ₂	253/4	$14^{1}/_{2}$	173/4	3	23/16	$7^{7}/_{32}$	$2^{1}/_{2}$	63/4	
J259T	21/8	11 ³ / ₈	19 ⁷ /8	291/16	81/4	29 ³ / ₄	$5^{3}/_{4}$	4	101/2	31/2	105/8	

			ORDERING IN	FORMATION*		
Cap.	Max Lift	Order	Strokes to Extend Piston	Handle Effort at Max Load	Carry	Product Wt.
Tons	Stroke	Number	1 in.	(lbs.)	Handle	(lbs.)
$5^{1}/_{2}$	81/4	J58T	8	83.9	Yes	43
11	91/4	J109T	13	88	Yes	64
$27^{1}/_{2}$	93/16	J259T	21	88	Yes	203